

Liberty Pumps®

LE70-Series

Sewage Pumps

**3/4 hp
2" Solids-Handling**

Features:

- Rugged 2 vane, semi-open cast iron impellers
- Cast iron housings and volute with all stainless and brass fasteners
- 416 stainless steel rotor shaft
 - Oil-filled, hermetically sealed motors
 - Built-in thermal protection on single phase models
 - 2" or 3" flanged discharge
- Permanently lubricated upper and lower ball bearings
 - Unitized shaft seals
- Single float mechanical level control with series plug for manual bypass operation—standard on single-phase automatic models
- Adjustable pumping range
- Quick-disconnect 10' standard power cord allows replacement of cord in seconds without breaking seals to motor. (25' length optional)



Models:

SINGLE PHASE

LE71M 115V, 12a, manual
LE71A 115V, 12a, automatic
LE72M 208-230V, 6a, manual
LE72A 208-230V, 6a, automatic

3-PHASE

LE73M 208-230V, 4.1a, manual*
LE74M 440-480V, 2.1a, manual*

*NOTE: 3-phase models require control panel for automatic operation. See sewage accessories literature for complete information on all Simplex and Duplex controls.

innovate. evolve.

LE70-SERIES TECHNICAL SPECIFICATIONS

ALL MODELS: 3/4 HP, 1725 RPM

PUMP

The pump(s) shall be model _____ as manufactured by Liberty Pumps, Bergen, N.Y. or equal. The pump(s) shall have a capacity of _____ GPM at a total dynamic head of _____ feet. Motor size shall be 3/4 horsepower, _____ phase, 60 hz. and _____ volt operation.

MOTOR

The pump motor shall be of the submersible type, oil filled, and hermetically sealed. Single phase motors shall have thermal overload protection embedded in the windings, and shall automatically reset when motor cools. Three-phase motors shall have heat breakers incorporated into the control panel, properly sized for the horsepower and amperage of the pump(s).

The rotor shaft shall be made of 416 stainless steel and shall be supported by a lower ball bearing, and an upper sleeve bearing.

The power cord shall be of the quick-disconnect design.

IMPELLER

The pump impeller shall be cast iron, 2 vane, semi-open, and shall be capable of passing a 2" spherical solid.

SEAL

The shaft seal shall be of the carbon/ceramic unitized design, with BUNA N elastomers and stainless housings.

EXTERNAL CONSTRUCTION

The pump volute, legs and motor housing shall be heavy gray iron castings, class 25 or better. All castings shall be powder coated before assembly.

All fasteners shall be of 300-series stainless steel.

LEVEL CONTROL

The pump shall be controlled by an adjustable mechanical switch sealed in a PVC float, and shall have a series plug for manual bypass operation.

	MODELS	VOLTS	PHASE	AMPS	DISCHARGE	AUTOMATIC
SINGLE PHASE	LE71M2	115	1	12	2" FLANGED	NO
	LE71A2	115	1	12	2" FLANGED	YES
	LE72M2	208-230	1	6	2" FLANGED	NO
	LE72A2	208-230	1	6	2" FLANGED	YES
	LE71M3	115	1	12	3" FLANGED	NO
	LE71A3	115	1	12	3" FLANGED	YES
	LE72M3	208-230	1	6	3" FLANGED	NO
	LE72A3	208-230	1	6	3" FLANGED	YES
3-PHASE	LE73M2	208-230	3	4.1	2" FLANGED	NO
	LE74M2	440-480	3	2.1	2" FLANGED	NO
	LE73M3	208-230	3	4.1	3" FLANGED	NO
	LE74M3	440-480	3	2.1	3" FLANGED	NO

10' cord standard on above models. For 25' cord options, add a "-2" suffix to model number.
Example: LE71A2-2 for Model LE71A2 with 25' cord.

NOTE: 3-Phase models require panel for automatic operation. See sewage accessories literature for complete information on all simplex and duplex controls.

DIMENSIONAL DATA:

Weight: LE71M: 60 LBS.

Height: 14.1"


Major Width: 12.5"

Maximum fluid temperature 140° F.

Dual Safety certification for the United States and Canada.



PERFORMANCE CURVE



Specifications are subject to change without notice.